

Mini Banker Safe is a low to medium security safe designed ideally for small businesses and homes to protect valuables and documents.



Mini Banker Safe

burglar resistant safe

Features

- Body** - The body has an effective barrier thickness of 65mm; constructed from steel, welded throughout to form a single unit and filled with Chubb's **F60** specially formulated barrier material.
- Door** - The door has an overall thickness of 75mm incorporating a 10mm solid steel plate. The front edge of the door is secured to the body by front moving bolts. A full length docking bolt secures the back edge of the door. Each front bolt measures 25mm in diameter.
- Locking** - Fitted with a 3-wheel Keyless Combination Lock protected by a Glass Relocker and a 8-levers Key Lock protected by a drill resistant manganese steel plate (except size 2, which

comes with only one of the two locks). Both locks operate independently of each other. The Relocker is further protected by a plate embedded with Tungsten Carbide pins. This further strengthens the drill resisting qualities of the Relocker.

- Fire Resistance** - Tested in accordance with the Japanese Industrial Standard JIS 1037:1989 for a 25 minutes fire rating.

- Fittings** - The safe comes complete with a standard internal steel shelf which is adjustable at intervals to suit individual customer requirements. A single lockable drawer is also included.

- Finish** - Comes with an epoxy based light grey paint. The paint is both scratch resistant and durable.




Chubb safes
Trusted the world over.


BURGLAR
RESISTANT

Product Specifications

Size	External (mm)					Internal (mm)					Nett weight (Kg)	
	(A) Height	(B) Width	(C) Depth	(D) Clear depth over furniture	(E) Furniture Projection	(F) Height	(G) Width	(H) Depth	(I) Door swing	(J) Depth with door at 90°		(K) Width when door is fully open
2	488	435	445	495	53	358	305	305	371	829	785	180
3	590	435	445	495	53	460	305	305	371	829	785	210
4	590	550	560	614	53	460	420	420	486	1059	1014	300
5	717	550	560	614	53	587	420	420	486	1059	1028	340
6	894	550	560	614	53	764	420	420	486	1059	1065	400
7	1047	640	650	702	53	917	510	510	576	1239	1205	540



DRAWINGS NOT TO SCALE



INTERNAL FITTING

Options

- Night Drawer Trap (NDT)** - Allow for effective deposit of cash and documents through a secured drawer without having to open the safe's main door. Upon closing the drawer, the contents would fall into the safe. An "Anti-Fishing Plate" is also incorporated to protect against "fishing" attempts to remove the safe's content through the Trap.
Drawer Clear Opening : 239mm (W) x 153mm (H) x 125mm (D)
Night Drawer Trap External Height : 254mm
- Envelope Slot** - Specially designed with a slit (1/2" [13mm] W x 6" [152mm] L) on the top surface of the safe to facilitate easy and convenient deposit of small amount of cash and other less bulky documents without having to open the safe. Like the NDT, an "Anti-Fishing Plate" is installed to protect against "fishing" attempts.
- An alarm kit may be incorporated into the safe for possible connection to the premise's main alarm system.
- A Blinder Shield and Dial Check Lock can be fitted to the combination lock as an option.
- A choice of two or three movement timelocks (restricted to size 6 & 7 only) may also be fitted as an additional requirement. Other electronically operated locks may also be fitted as an option.



Keyless Combination Lock



Key Lock

Keyless Combination Lock

Secured by one 3-wheel Keyless Combination Lock listed under UL Group 2, VdS class 1, Cen A, A2PA. Capable of 1,000,000 changes of code. The operation of this lock is simple. The code can be changed easily and security can be maintained over the safe whenever there is a change of staff.

Key Lock

Secured by one 8-levers double bitting Key Lock certified under EN 1300 A, ECB-S, CNP a2p (E) Niveau A, VdS class 1, GOST class B, IMP class A, UL 437.

Authorised dealer:

Note: Chubb's policy is one of constant improvement. We reserve the right to alter any specification contained in this publication without prior notification. Variance ± 5mm.

Chubb safes
Trusted the world over.

Gunnebo Singapore Pte Ltd
8 Shenton Way #17-01 Temaseck Tower
Singapore 068811
Tel: +65-6327 9119 Fax: +65-6233 9428
Email: gun@gunnebo.com
Website: www.gunnebo.com

*Chubb is a registered trademark owned by Chubb plc and is used under license

GUNNEBO
For a safer world.